



MASSEY FERGUSON

MASSEY FERGUSON 1GC SERIES // 23-25 HP

Big Capability In a Small Package

The Massey Ferguson® 1GC Series delivers the perfect blend of power, versatility and affordability to make it the right choice for landowners who need a reliable, comfortable tractor capable of handling a variety of jobs.

COMFORT

- » Wide, tall comfortable seat for better support and less fatigue
- » Spacious operator station puts necessary controls right at your fingertips
- » Cruise control allows for more steady operation during long days
- » Ground-level fueling

VERSATILITY

- » Wide range of compatible attachments, including mid-mount mowers, skid steer loader bucket and backhoe
- » Compact size makes it easier to maneuver in tight spaces
- » 2000 rpm mid-PTO
- » Independent 540 rpm rear PTO
- » Integrated loader joystick

EASE OF USE

- » 1.1L, 3-cylinder liquid-cooled Iseki diesel engine
- » 2-range hydrostatic transmission with side-by-side pedals
- » Sleek, easy-to-use instrument panel
- » Front aux power outlet



GET MORE INFORMATION

SCAN HERE TO LEARN MORE ABOUT THE MF 1GC OR TO FIND YOUR LOCAL DEALER.



BORN TO **FARM**

TECHNICAL SPECIFICATIONS

		MF 1GC.23	MF 1GC.23 TLB	MF 1GC.25	MF 1GC.25 TLB
ENGINE		Iseki 1.1L 3-cylinder liquid-cooled diesel			
Rated Engine Power	HP (kW)	22.5 (16.8)		24.5 (18.6)	
Rated Engine Speed	rpm	2,600		3,000	
PTO Power	HP (kW)	18.3 (13.6)		18.5 (13.8)	
Fuel Tank Capacity	L (gal.)	25 (6.6)			
TRANSMISSION		2-range hydrostatic transmission			
Side-by-Side Foot Pedals		Yes			
Cruise Control		Yes			
HITCH AND HYDRAULICS					
Hydraulic Flow	LPM (GPM)	22.7 (6.0)		26.3 (6.9)	
3-Point-Hitch Type		Cat 1			
3-Point-Hitch Lift Capacity (At Lift Points)	kg (lbs.)	540 (1,191)			
3-Point-Hitch Lift Capacity (24 in. Behind Lift Point)	kg (lbs.)	300 (661)			
PTO					
Rear		540 rpm, 1.375 in., six splines			
Mid		2000 rpm, 1 in., 15 splines			
OPERATORS STATION		Platform			
ROPS		Fixed	Folding	Fixed	Folding
TIRES		Agricultural, Turf & Industrial			
Front Dimensions		18 x 8.50 — 10			
Rear Dimensions		26 x 12.00 — 12			

ATTACHMENTS

	LOADER	FL1803	BACKHOE	BH2720
Tool Carrier		Skid steer	Control Type	SAE with boom float
Bucket Width	in.	48	Digging Depth	cm (in.)
Maximum Lift Height — Pivot Pin	mm. (in.)	1,880 (74)	Max Reach	cm (in.)
Maximum Dump Angle		43°	Bucket Digging Force	kg (lbs.)
Maximum Rollback Angle		30°	Boom Digging Force	kg (lbs.)
Digging Depth	mm (in.)	50 (2)	Loading Height	cm (in.)
Lift Capacity to Maximum Height — Pivot Pins	kg (lbs.)	418 (922)	Transport Height	cm (in.)
Lift Capacity to Maximum Height — 19.5 in. Forward	kg (lbs.)	282 (622)	Swing Arc	150°
Breakout Force — Pivot Pins	kg (lbs.)	631 (1,392)	Bucket Rotation	177°
Breakout Force — 19.5 in. Forward	kg (lbs.)	423 (932)	Bucket Widths	in.
Lift Cylinder Diameter	mm (in.)	40 (2 x 1.57)	Compatible Models	1GC.23 TLB, 1GC.25TLB
Bucket Cylinder Diameter	mm (in.)	40 (2 x 1.57)		
MID-MOUNT MOWER		2320	2326	
Discharge		Right side	Right side	
Drive Over Install	in.	No	Yes	
Cutting Width	mm (in.)	1,371 (54)	1,524 (60)	
Cutting Height	mm (in.)	30-120 (1.2-4.7)		
Number of Blades		3		
Transport Height	mm (in.)	150 (5.9)		
Blade Tip Speed	m/s	87	89	

*Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification.